HINKLEY&R.

HINKLEY LIGHTING, INC. 33000 PIN OAK PARKWAY | AVON LAKE, OHIO 44012 [PH] 330.653.5500 [F] 440.653.5555 HINKLEYLIGHTING.com | FREDRICKRAMOND.com

Nuvi Medium Deck Sconce 10-Pack 15446BZ-10

| ITEM NUMBER15446BZ-10BRANDHinkley LightingMATERIALVinyl AlloyHEIGHT0.8"WIDTH5.0"LED COLOR TEMP2700.0000VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet Rated• Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards• Rated for both indoor and outdoor use• Photometrics are based off engine photometrics at various mounting height• Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.• Easy and efficient installation: fewer fixtures illuminate a more extensive aread offering a diverse range of mounting opportunities. | |
|--|----|
| MATERIALVinyl AlloyHEIGHT0.8"WIDTH5.0"LED COLOR TEMP2700.0000VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet Rated• Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards• Rated for both indoor and outdoor use• Photometrics are based off engine photometrics at various mounting height• Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.• Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| HEIGHT0.8"WIDTH5.0"LED COLOR TEMP2700.0000VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet RatedSuitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety StandardsRated for both indoor and outdoor usePhotometrics are based off engine photometrics at various mounting heightDurable, solid vinyl alloy construction, making the fixture suitable for harsh environments.Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| WIDTH5.0"LED COLOR TEMP2700.0000VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet RatedSuitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety StandardsRated for both indoor and outdoor usePhotometrics are based off engine photometrics at various mounting heightDurable, solid vinyl alloy construction, making the fixture suitable for harsh environments.Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| LED COLOR TEMP2700.0000VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet RatedSuitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety StandardsRated for both indoor and outdoor use Photometrics are based off engine photometrics at various mounting heightDurable, solid vinyl alloy construction, making the fixture suitable for harsh environments.FEATURES AND BENEFITSEasy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| VOLTAGE12vLED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet RatedSuitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards • Rated for both indoor and outdoor use • Photometrics are based off engine photometrics at various mounting height • Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.FEATURES AND BENEFITS• Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| LED LUMENS140WATTAGE1.90w LED *IncludedCERTIFICATIONC-US Wet Rated• Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards • Rated for both indoor and outdoor use • Photometrics are based off engine photometrics at various mounting height • Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.FEATURES AND BENEFITS• Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| WATTAGE 1.90w LED *Included CERTIFICATION C-US Wet Rated Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards Rated for both indoor and outdoor use Photometrics are based off engine photometrics at various mounting height Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments. Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| CERTIFICATIONC-US Wet Rated• Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards • Rated for both indoor and outdoor use • Photometrics are based off engine photometrics at various mounting height • Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.FEATURES AND BENEFITS• Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| CERTIFICATIONC-US Wet Rated• Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards • Rated for both indoor and outdoor use • Photometrics are based off engine photometrics at various mounting height • Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments.FEATURES AND BENEFITS• Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| Suitable for use in wet (interior direct splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards Rated for both indoor and outdoor use Photometrics are based off engine photometrics at various mounting height Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments. Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| splash and outdoor direct rain or sprinkle locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standard Association Product Safety Standards Rated for both indoor and outdoor use Photometrics are based off engine photometrics at various mounting height Durable, solid vinyl alloy construction, making the fixture suitable for harsh environments. Easy and efficient installation: fewer fixtures illuminate a more extensive area offering a diverse range of mounting | |
| Exceptional 12V LED horizontal illumination due to innovative composite optic technology Available as single items or packages of For complete warranty information visit (hyperlink) LED integrated components carry a 10- year limited warranty Lifetime warranty Warm rich light bronze tone | S. |
| LENGTH 3.0 | |
| FINISH Bronze | |
| | |



life Aglow®