


CAUTION – RISK OF SHOCK –

Disconnect Power at the main circuit breaker panel or main fuse box before starting and during the installation.

- 1) Rotate frame and sockets into the desired position.
- 2) Pass fixture electrical wire and ground wire through desired amount of stems D & E and screw together using supplied threaded nipples into coupler on top of fixture.
- 3) Screw in two (2) canopy mounting screws into the mounting strap and connect mounting strap to outlet box.
- 4) Connect the two (2) loops, chain link with two (2) threaded nipples to the canopy using the lockwasher and hexnut supplied.
- 5) Route wires and ground wire through chain link and through canopy into the electrical box. Connect the D & E stems to the lower loop.
- 6) Make wire connections. Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)



- 7) Use the (2) two ball knobs and two (2) lockwashers to secure canopy after wire connections are completed per below.
- 8) Install approved bulb (not included).

