


### CAUTION – RISK OF SHOCK –

Disconnect Power at the main circuit breaker panel or main fuse box before starting and during the installation.

- 1) Pass fixture wire and ground wire thru desired amount of stems D & E and thread together using supplied nipples. **NOTE:** Use a drop of Thread compound (supplied) on the threads.
- 2) Thread Swivel onto stems securely. Pass threaded Swivel, wire, ground wire thru hole in canopy. Place lockwasher onto end of threaded nipple protruding from inside canopy. Thread hexnut onto threaded nipple protruding from inside canopy if not already completed by factory. Tighten to secure Swivel.
- 3) Find the appropriate threaded holes on mounting strap. Assemble mounting screws into threaded holes.
- 4) Attach mounting strap to outlet box. Mounting strap can be adjusted to suit position of fixture.
- 5) Make wire connections. Reference chart below for correct connections and wire accordingly.

Connect Black or Red Supply Wire to:	Connect White Supply Wire to:
Black	White
*Parallel cord (round & smooth)	*Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer	Clear, Brown, Gold or Black with tracer
Insulated wire (other than green) with copper conductor	Insulated wire (other than green) with silver conductor

\*Note: When parallel wires (SPT I & SPT II) are used. The neutral wire is square shaped or ridged and the other wire will be round in shape or smooth (see illus.)



- 6) Push fixture to ceiling, carefully passing mounting screws through holes in canopy. Make sure all wires are inside canopy and do not get pinched between canopy and ceiling.
- 7) Thread lockup knobs and lockwashers onto mounting screw and tighten to secure fixture to ceiling.
- 8) Place glass over socket and take the glass retainer and socket ring and thread onto the socket to secure glass in place.
- 9) Screw light bulb (not supplied) in place.

