## **INSTALLATION INSTRUCTION FOR N3713**

# WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER. AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES <u>OU DU DISJONCTEUR</u>.

#### READ AND SAVE THESE INSTRUCTIONS

#### **PREPARATION**

- Shut off the power at the fuse box or circuit breaker box. If necessary, remove the existing fixture and its mounting hardware from the ceiling.
- Carefully remove the new fixture from the carton and check that all parts are included as shown in the illustration.

## **ASSEMBLING THE FIXTURE (Fig. 1)**

- 3. Thread the center rod (O) onto the nipple (P), then thread the coupling (N) into the center rod (O).
- 4. Secure the coupling (G) of the arms (J) to the coupling (F) using screws (H).

## **MOUNTING THE FIXTURE (Fig.1)**

- 4. Thread the two mounting screws (A) (Size: #8-32\*1.3"L) half way into the pre-drilled holes in the circular strap (B) spaced the same distance apart as the holes in the fixture canopy (D).
- Attach the circular strap (B) to the outlet box (not provided) using the outlet box screws (C) (Size: #8-32\*0.6"L) through the slotted holes. The side of the circular strap (B) marked "GND" must face out.

### **CONNECTING THE WIRES (Fig. 2)**

6. Connect the electrical wires as shown in Fig. 2, making sure all wire connectors are secured. If your outlet box has a ground wire (green or bare copper), connect the fixture's ground wire to it. Otherwise, connect the fixture's ground wire directly to the circular strap (B) using the green screw provided. After the wires are connected, tuck them neatly inside the outlet box.

#### **COMPLETING THE INSTALLATION (Fig. 1)**

- 6. Place the canopy (D) onto the mounting screws (A) and secure with the finials (E).
- 7. Raise the shade (M) and connect the hooks (K) of the arms (J) to the loops (L).
- 8. Install the light bulb(s) (not included) in accordance with the fixtures specifications (DO NOT EXCEED THE MAXIMUM WATTAGE!) (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)

Your installation is now complete. Return the power to the outlet box and test the fixture.





