BWO40S22P2 ~ BWO40S22A2 BWO40S45P2 ~ BWO40S45A2 BWO40S61P2 ~ BWO40S61A2

SPECIFICATIONS



Ø3" **FLEXIBLE** Ø2 3/4" · JOINT **HEIGHT ADJUSTMENT**

Ø2 3/4"-

Ø3" ·

SCREW

FERRULE INSTALLATION

TOOL

AND BENEFITS:

- AVAILABLE IN ABS AND PVC
- AVAILABLE IN MANY FINISHES
- IAPMO AND CSA LISTED
- FITS TUBS 12"-33" DEEP
- FLEXIBLE BALL JOINT ON OVERFLOW FOR BETTER FIT ON TUB ANGLE
- FITS TUBS UP TO 1" THICK
- FOR ACRYLIC, CAST IRON, FIBERGLASS & STEEL **TUBS AND WHIRLPOOLS**

TWO FERRULE SIZES FOR TUBS UP TO 1" THICK 28 FERRULE 1 1/8" 35 FERRULE 1 3/8"

> Ø1 1/2" PIPE NOT **SUPPLIED**

MODEL NO	DIM A*	DIM B*	CABLE LENGTH
BWO40S22P2	12"-22"	7"-12"	27"
BWO40S45P2	22"-27"	7"-12"	39"
BWO40S61P2	28"-33"	7"-12"	50"
*VARIES DEPENDING ON TUB SIZE			

WARRANTY

Α*

ONE YEAR WARRANTY ON PLATED FINISHES, 90 DAY WARRANTY ON ORB, EB, MHB, TB AND WCP AND LIFETIME ON PVD PROVIDED PROPER CARE HAS BEEN USED. ONE YEAR WARRANTY ON ALL PARTS. WARRANTY APPLIES TO ORIGINAL PURCHASER AND CLAIMS REQUIRE PROOF OF PURCHASE.

2 1/2"