

# NL-3326

## 3" Frosted Flat Lens with Reflector

### FEATURES

**Trim:** Precision spun 0.050 aluminum high grade reflector that includes a frosted flat lens. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

**Mounting:** Trim includes three trim clips that securely mount trim in housing.

### COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

### LAMP

#### Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

#### Low Voltage

**Important:** Do not use glass lens (provided) when already using lamp with glass cover  
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

### LABELS AND LISTINGS

cULus Listed for Wet Location when used with compatible housing.



Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_


### PRODUCT IMAGES AND DIMENSIONS



NL-3326G



NL-3326W



## 3" Frosted Flat Lens with Reflector

Catalog No. \_\_\_\_\_

**NL-3326BZ** = Frosted Flat Lens with Specular Clear Reflector and Bronze Metal Ring

**NL-3326G** = Frosted Flat Lens with Specular Clear Reflector and Gold Metal Ring

**NL-3326W** = Frosted Flat Lens with Specular Clear Reflector and White Metal Ring

## Compatible Housings

### Line Voltage

Catalog No. \_\_\_\_\_

**NH-350AT** = 3" Non-IC Air-Tight New Construction Housing / 50W max.

**NHIC-350AT** = 3" IC Air-Tight New Construction Housing / 50W max.

**NHR-354AT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

### Low Voltage

Catalog No. \_\_\_\_\_

**NLIC-301AT/1EL** = 3" IC Air-Tight New Construction Housing / 50W max.

**NLIC-301QAT/20** = 3" IC Air-Tight New Construction Housing / 20W max.

**NLIC-301QAT/37** = 3" IC Air-Tight New Construction Housing / 37W max.

**NLIC-301QAT** = 3" IC Air-Tight New Construction Housing / 50W max.

**NL-301AT/1EL** = 3" Non-IC Air-Tight New Const. Housing / 50W max.

**NL-301QAT/20** = 3" Non-IC Air-Tight New Const. Housing / 20W max.

**NL-301QAT/37** = 3" Non-IC Air-Tight New Const. Housing / 37W max.

**NL-301QAT** = 3" Non-IC Air-Tight New Const. Housing / 50W max.

**NLR-304AT/1EL** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

**NLR-304QAT/20** = 3" Non-IC Air-Tight Remodel Housing / 20W max.

**NLR-304QAT/37** = 3" Non-IC Air-Tight Remodel Housing / 37W max.

**NLR-304QAT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

**NLR-305AT/20** = 3" Non-IC Air-Tight Remodel Housing / 20W max.

**NLR-305AT/37** = 3" Non-IC Air-Tight Remodel Housing / 37W max.

**NLR-305AT** = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: **NL-3326BZ** = 3" Frosted Flat Lens with Specular Clear Reflector and Bronze Metal Ring