


NL-3345 Adjustable Slot Aperture

Type
Project
Catalog No.
Lamp/Wattage

TRIM DIMENSIONS



Trim OD: 3-5/8"
Height: 1-5/8"



FEATURES

Trim
Metal trim with 1-1/8" x 1-3/4" slot aperture that can rotate 358° horizontally. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in metal, may also be used with custom combination of ring finishes.

Mounting
Trim includes three trim clips that securely mount trim in housing.

Compatible Housings
Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

Lamp
Line Voltage
50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)
Low Voltage
IMPORTANT: DO NOT USE GLASS LENS (PROVIDED) WHEN ALREADY USING LAMP WITH GLASS COVER
20W-50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series)

Labels and Listings
cULus Listed for Damp Location when used with compatible housing.

Compatible Housings

LINE VOLTAGE			
Item Number	Installation Type	Lamp	Dimensions
NH-350AT	Non-IC Air-Tight New Const.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NHIC-350AT	IC Air-Tight New Construction	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NHR-354AT	Non-IC Air-Tight Remodel	50W MR16	W: 4-1/4" L: 11-1/4" H: 5-5/8"
LOW VOLTAGE			
NL-301QAT/20	Non-IC AT New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT/37	Non-IC AT New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301QAT	Non-IC AT New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NL-301AT/1EL	Non-IC AT New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 5-5/8"
NLIC-301QAT/20	IC Air-Tight New Const., Mag.	20W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT/37	IC Air-Tight New Const., Mag.	37W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301QAT	IC Air-Tight New Const., Mag.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLIC-301AT/1EL	IC Air-Tight New Const., Elec.	50W MR16	W: 6-3/8" L: 16" H: 8-1/8"
NLR-304QAT/20	Non-IC Air-Tight Remodel, Mag.	20W MR16	W: 4-1/4" L: 11-1/4" H: 4-5/8"
NLR-304QAT/37	Non-IC Air-Tight Remodel, Mag.	37W MR16	W: 4-1/4" L: 11-1/4" H: 4-5/8"
NLR-304QAT	Non-IC Air-Tight Remodel, Mag.	50W MR16	W: 4-1/4" L: 11-1/4" H: 4-5/8"
NLR-304AT/1EL	Non-IC Air-Tight Remodel, Elec.	50W MR16	W: 4-1/4" L: 11-1/4" H: 4-5/8"

Adjustable Slot Aperture

- NL-33458B: Black Adjustable Slot Aperture with Black Metal Ring
- NL-3345BZ: Bronze Adjustable Slot Aperture with Bronze Metal Ring
- NL-3345C: Chrome Adjustable Slot Aperture with Chrome Metal Ring
- NL-3345CO: Copper Adjustable Slot Aperture with Copper Metal Ring
- NL-3345G: Gold Adjustable Slot Aperture with Gold Metal Ring
- NL-3345N: Natural Metal Adjustable Slot Aperture with Natural Metal Ring
- NL-3345W: White Adjustable Slot Aperture with White Metal Ring